

# REFRIGERATION REFRIGERATORS

PLANET 70 cm. depth  
-2 ÷ +8°C / -12 ÷ -24°C









REFRIGERATOR 'PLANET' 600 LT,  
SINGLE DOOR





REFRIGERATOR 'PLANET' 1300 LT, 2  
DOORS

One-piece construction entirely in stainless steel AISI 304 18-10. Shelf supports in stainless steel, 20 levels for shelves or containers. Ventilated cooling system with **evaporator** positioned **outside the refrigerating chamber**. 'Intelligent' defrosting when needed by hot gas. Automatic evaporation of condense drain. Tropicalization class: +43°C max. **HACCP** electronic control panel. Internal lighting and key-operated lock. **Hyper Cold** function and **Energy Saving System**. Guides and shelves standard supplied: nr. 3 each comp. Mod. PD130/ PD130B: +3 connecting shelves.

MOD.							
<b>PD60</b>	75x70x204	-2/+8°C	I 600	W 429	0,46	1	<b>1</b>
<b>PD60B</b>	75x70x204	-12/-24°C	I 600	W 752	0,72	1	
<b>PD130</b>	150x70x204	-2/+8°C	I 1300	W 566	0,71	1	<b>2</b>
<b>PD130NN</b>	150x70x204	-2/+8;-2/+8°C	I 1300	W 429+429	0,92	1	
<b>PD130B</b>	150x70x204	-12/-24°C	I 1300	W 1477	1,8	1	
<b>PD130BN</b>	150x70x204	-2/+8;-12/-24°C	I 1300	W 752+429	1,18	1	

## ACCESSORIES

MOD.		Description	
<b>ST02</b>		KIT TEMPERATURE-RECORDER WITH PRINTER 2 CHANNELS	1
<b>CGX70</b>		TWO S/S SHELF SLIDES FOR SHELVES AND CONTAINERS	
<b>GP70</b>	53x55x6,4	CLASSED FOODSAFE PLASTIC-COATED SHELF	
<b>GPR70</b>		PLASTIC COATED CONNECTING SHELF	
<b>C151</b>	32x53x15	S/S 1/1 GN WIRE BASKET	
<b>PPRX140</b>		ST/ST EXTRA FOOT FOR 2 COLUMN REFRIG., LOADS<200KG	
<b>KRPRVX</b>		KIT OF 4 SWIVELLING WHEELS, ON ST/STEEL PLATE	
<b>KPAF</b>		PEDAL OPENING FOR REFRIGERATORS	



II-2007 119

# REFRIGERATION REFRIGERATORS

PLANET 80 cm depth 2/1 GN  
-2 ÷ +8°C / -12 ÷ -24°C  
-6 ÷ +6°C ..CP, 0 ÷ +10°C ..PV

Shelf supports in st/st, 20 levels for shelves or ctnr (exc. mod.PD150CP: 10+7+3 levels for fish ctnr). Ventilated cooling with **evaporator** positioned **outside** the refig.chamber. 'Intelligent' defrosting when needed by hot gas. Automatic evaporation of condense drain. Trop. max +43°C, +32°C mod.'PV'. **HACCP** electronic control panel. Internal lighting and key-operated lock. **Hyper Cold** and **Energy Saving System**. Guides and shelves 2/1 GN standard supplied: nr. 3 each comp. (exc. mod. PD150CP: 5 guides/shelves and 6 containers/3 guides for the fish comp.). Mod. PD150/ PD150B/150PV: +3 connecting shelves.



REFRIGERATOR "PLANET" 2/1 700  
LTS, SINGLE DOOR




REFRIGERATOR 'PLANET' 2/1 700 LT,  
SINGLE GLASS DOOR



'PLANET' REFRIG. 2/1 1150+350 LT, 2  
DOORS & FISH STOR.



REFRIGERATOR 'PLANET' 2/1 1500 LT,  
120 II-2007 2 GLASS DOORS

MOD.							
PD70	75x80x204	-2/+8°C	I 700	W 429	0,46	1	1
PD702	75x80x204	-2/+8°C	I 700	W 429	0,46	1	
PD70B	75x80x204	-12/-24°C	I 700	W 752	0,72	1	
PD70B2	75x80x204	-12/-24°C	I 700	W 752	0,75	1	
PD70PV	75x80x204	0/+10°C	I 700	W 429	0,56	1	2
PD150	150x80x204	-2/+8°C	I 1500	W 566	0,71	1	
PD150NN	150x80x204	-2/+8;-2/+8°C	I 1500	W 429+429	0,92	1	
PD150B	150x80x204	-12/-24°C	I 1500	W 1477	1,8	1	
PD150BN	150x80x204	-2/+8;-12/-24°C	I 1500	W 752+429	1,18	1	
PD150BB	150x80x204	-12/-24;-12/-24°C	I 1500	W 752+752	1,44	1	
PD150CP	150x80x204	-6/+6;-2/+8°C	I 1500	W 429+429	0,46	1	3
PD150PV	150x80x204	0/+10°C	I 1500	W 566	0,86	1	4

# REFRIGERATION REFRIGERATORS

PLANET 80 cm depth 2/1 GN for  
REMOTE COOLING  
-2 ÷ +8°C / -12 ÷ -24°C



REMOTE REFRIGERATOR PLANET 2/1  
700 LT, SINGLE DOOR



REMOTE REFRIGERATOR PLANET 2/1  
1500 LTS, 2 DOORS

..”R”: SUITABLE FOR REMOTE  
COOLING UNIT, PLACED AT A  
DISTANCE 10 MT MAX.



One-piece construction entirely in st/st AISI 304 18-10. Shelf supports in st/st 20 levels for shelves or containers 2/1 GN. Ventilated cooling with **evaporator** positioned **outside** the refig. chamber. Electric-type 'intelligent' defrosting by heating elements, when needed. Automatic evaporation of condense drain. Tropic. class: +43°C max. HACCP electronic control panel. Internal lighting and key-operated lock. **Hyper Cold** and **Energy Saving System**. Guides/shelves 2/1 GN standard supplied: nr. 3 each compartment. Mod. PD150R/PD150BR: +3 connecting shelves.

MOD.							
<b>PD70R</b>	75x80x204	-2/+8°C	1700	W 429*	0,16	1	<b>1</b>
<b>PD70BR</b>	75x80x204	-12/-24°C	1700	W 752*	0,24	1	
<b>PD150R</b>	150x80x204	-2/+8°C	1500	W 566*	0,2	1	<b>2</b>
<b>PD150BR</b>	150x80x204	-12/-24°C	1500	W 1477*	0,3	1	

\*= Cooling power if the unit is connected to cooling unit Angelo Po GR..

## ACCESSORIES

MOD.		Description	
<b>GR65TN4</b>		REMOTE COOLING UNIT, POSITIVE TEMPERATURE	1
<b>GR65BT</b>		REMOTE COOLING UNIT, NEGATIVE TEMPERATURE	1 •
<b>GR140TN4</b>		REMOTE COOLING UNIT, POSITIVE TEMPERATURE	1
<b>GR135BT</b>		REMOTE COOLING UNIT, NEGATIVE TEMPERATURE	1 •
<b>ST02</b>		KIT TEMPERATURE-RECORDER WITH PRINTER 2 CHANNELS	1
<b>KCGR</b>	44x64,5x100	REMOTE COOLING UNIT COVERING	






II-2007 121

# REFRIGERATION REFRIGERATORS

## ACCESSORIES PLANET PROF 80 cm

### ACCESSORIES

MOD.		Descrizione	€
CGX	4x65x3	TWO S/S SHELF SLIDES FOR SHELVES AND CONTAINERS	29
GP21	53x65x0	PLASTIC COATED SHELF 2/1 GN CLASSED FOODSAFE	35
GP21B	53x65x0	PLASTIC COATED SHELF 2/1 GN FOR VERT.BOTTLES	37
G785X		2/1 GN STAINLESS STEEL SHELF	64
GPR		PLASTIC- COATED CONNECTING SHELF	18
GC80X	53x65x0	ST/STEEL 2/1 GN MEAT HANGING SHELF WITH 4 HOOKS	120
BP21	53x65x20	PLASTIC CONTAINER 2/1 GN, WITHOUT LID	95
BGN11P	53x32,5x15	TWO PLASTIC FOODSAFE 1/1 GN CONTAINERS WITHOUT LID	101
C151	32x53x15	S/S 1/1 GN WIRE BASKET	76
MAFPS4		UPRIGHTS FOR PASTRY USE OF REFRIGERATOR	208
CGPS		COUPLE OF GUIDES FOR PASTRY CONTAINERS	15
KRPRVX		KIT OF 4 SWIVELLING WHEELS, ON ST/STEEL PLATE	215
PPRX140		ST/ST EXTRA FOOT FOR 2 COLUMN REFRIG., LOADS<200KG	22
KPAF		PEDAL OPENING FOR REFRIGERATORS	176



122 II-2007