

REFRIGERATION REFRIGERATORS

MOON 73,5 cm depth
-2 ÷ +8°C / -15 ÷ -22°C







One-piece construction entirely in st/st AISI 304 18-10. Removable shelf supports in st/st, 20 levels for shelves or ctrn. Ventilated cooling system. Electric-type automatic defrosting by heating elements. Automatic evaporation of condense drain. Tropicalization class: +43°C max. Internal lighting and key-operated lock. Control board equipped with digital thermometer-thermostat. Guides/shelves standard supplied: nr.3 each compartment.





REFRIGERATOR 'MOON' 600 LT,
SINGLE DOOR



FREEZER 'MOON' 1300 LT, 2 DOORS

MOD.							
MD60	75x73,5x204	-2/+8°C	1600	W 351	7	1	1
MD60B	75x73,5x204	-15/-22°C	1600	W 654	0,65	1	
MD130	150x73,5x204	-2/+8°C	1300	W 582	0,57	1	
MD130NN	150x73,5x204	-2/+8;-2/+8°C	1300	W 351+351	1,2	1	
MD130B	150x73,5x204	-15/-22°C	1300	W 1125	1,1	1	2
MD130BN	150x73,5x204	-2/+8;-15/-22°C	1300	W 654+351	1,15	1	

ACCESSORIES

MOD.		Description	
ST02		KIT TEMPERATURE-RECORDER WITH PRINTER 2 CHANNELS	1
CGX70		TWO S/S SHELF SLIDES FOR SHELVES AND CONTAINERS	
GPR70		PLASTIC COATED CONNECTING SHELF	
GP70	53x55x6,4	CLASSED FOODSAFE PLASTIC-COATED SHELF	
C151	32x53x15	S/S 1/1 GN WIRE BASKET	
PPRX140		ST/ST EXTRA FOOT FOR 2 COLUMN REFRIG., LOADS<200KG	
KPAF		PEDAL OPENING FOR REFRIGERATORS	
KRPRVX		KIT OF 4 SWIVELLING WHEELS, ON ST/STEEL PLATE	



II-2007 123

REFRIGERATION REFRIGERATORS

MOON 83,5 cm depth 2/1 GN

-2 ÷ +8°C / -15 ÷ -22°C

-6 ÷ +6°C ..CP, 0 ÷ +10°C ..PV

One-piece construction entirely in st/st AISI 304 18-10. Removable shelf supports in st/st, 20 levels for shelves or containers 2/1 GN. ..CP fish comp models: shelf support 5 pos. (mod. MD70CP and MD150NCP) or 3 pos. (mod. MD70NCP) for telescopic guides/fish ctr. Ventilated cooling system. Electric-type automatic defrosting by heating elements. Automatic evaporation of condense drain. Tropic. class: +43°C max, + 32°C mod. 'PV'. Internal lighting and key-operated lock.



REFRIGERATOR 'MOON' 2/1 700 LTS,
2 DOORS



'MOON' REFRIG. 2/1 350+350 LT, POS.
COMP. & FISH STOR.



'MOON' REFRIG. 2/1 GN 700 LT FOR
FISH STORAGE



FREEZER 'MOON' 2/1 700 LT, SINGLE
GLASS DOOR

MOD.							
MD70	75x83,5x204	-2/+8°C	1 700	W 351	0,5	1	
MD702	75x83,5x204	-2/+8°C	1 700	W 351	0,5	1	1
MD70NN	75x83,5x204	-2/+8;-2/+8°C	1 700	W 351+351	1	1	
MD70NB	75x83,5x204	-2/+8;-15/-22°C	1 700	W 351+654	1,1	1	
MD70B	75x83,5x204	-15/-22°C	1 700	W 654	0,65	1	
MD70NCP	75x83,5x204	-6/+6;-2/+8°C	1 700	W 351+351	1,1	1	2
MD70CP	75x83,5x204	-6/+6°C	1 700	W 582	0,57	1	3
MD70PV	75x83,5x204	0/+10°C	1 700	W 351	0,7	1	
MD70BPV	75x83,5x204	-10/-20°C	1 700	W 654	0,8	1	4

Control board equipped with digital thermometer-thermostat.
 2/1 GN shelves standard supplied:
 nr.3 each comp., except for:
 MD70CP: 5 telescopic drawers/10
 ctrn. MD70NCP: 2 guides/shelves
 and 3 telescopic drawers/6 ctrn
 MD150NCP: 3 guides/ shelves, 3
 telescopic drawers/6 ctrn.



REFRIGERATOR 'MOON' 2/1 GN 1500
 LTS, 2 DOORS









'MOON' REFRIGERATOR 2/1GN
 700+700 LT,2 COMP/2 DOOR



'MOON' REFRIG.2/1 1150+350
 LT,POS.COMP.&FISH STOR.



FREEZER 'MOON' 2/1 1500 LT, 2
 GLASS DOORS

MOD.							
MD150	150x83,5x204	-2/+8°C	l 1500	W 582	0,57	1	5
MD150NN	150x83,5x204	-2/+8;-2/+8°C	l 1500	W 351+351	1,1	1	6
MD150B	150x83,5x204	-15/-22°C	l 1500	W 1140	1,1	1	
MD150BN	150x83,5x204	-2/+8;-15/-22°C	l 1500	W 654+351	1,15	1	
MD150BB	150x83,5x204	-15/-22;-15/-22°C	l 1500	W 654+654	1,3	1	
MD150NCP	150x83,5x204	-6/+6;-2/+8°C	l 1500	W 351+582	1,1	1	7
MD150PV	150x83,5x204	0/+10°C	l 1500	W 582	0,7	1	
MD150BPV	150x83,5x204	-10/-20°C	l 1500	W 1477	1,25	1	8



REFRIGERATION REFRIGERATORS

MOON 83,5 cm depth 2/1 GN
-2 ÷ +8°C / -15 ÷ -22°C

One-piece construction entirely in stainless steel AISI 304 18-10. Removable shelf supports in stainless steel, 20 levels for shelves or containers 2/1 GN. Ventilated cooling system. Electric-type automatic defrosting by heating elements. Automatic evaporation of condense drain. Tropicalization class: +43°C. Internal lighting and key-operated lock. Control board equipped with digital thermometer-thermostat. 2/1 GN shelves standard supplied: nr. 3 each compartment.



REMOTE REFRIGERATOR 'MOON' 2/1
700 LT, SINGLE DOOR



REMOTE REFRIGERATOR 'MOON' 2/1
1500 LTS, 2 DOORS

MOD.						
MD70R	75x83,5x204	-2/+8°C	I 700	W 669	0,1	1
MD70BR	75x83,5x204	-15/-22°C	I 700	W 752	0,1	1
MD150R	150x83,5x204	-2/+8°C	I 1500	W 919	0,1	1
MD150BR	150x83,5x204	-15/-22°C	I 1500	W 1477	0,22	1

ACCESSORIES

MOD.		Description		
GR65TN4		REMOTE COOLING UNIT, POSITIVE TEMPERATURE	1	
GR65BT		REMOTE COOLING UNIT, NEGATIVE TEMPERATURE	1	
GR140TN4		REMOTE COOLING UNIT, POSITIVE TEMPERATURE	1	
GR135BT		REMOTE COOLING UNIT, NEGATIVE TEMPERATURE	1	
ST02		KIT TEMPERATURE-RECORDER WITH PRINTER 2 CHANNELS	1	
KCGR	44x64,5x100	REMOTE COOLING UNIT COVERING		



.."R": SUITABLE FOR REMOTE COOLING UNIT, AT A DISTANCE OF 25 MT MAX.



126 II-2007